Simulations of SSLV Ascent and Debris Transport

Space Shuttle Return-To-Flight



Stuart Rogers
Michael Aftosmis
Scott Murman
William Chan

NASA Advanced Supercomputing Division

NASA Ames Research Center

Reynaldo Gomez
Darby Vicker
Phil Stuart
Jim Greathouse

NASA Johnson Space Center

Seminar in Fluid Mechanics
Stanford University
October 11, 2005

Outline

- CFD simulations of the Space Shuttle Launch Vehicle ascent
- Debris transport analysis
- Debris aerodynamic modeling



CFD Analysis of SSLV Ascent



Motivation

- Predict air-loads on the redesigned External Tank
- Roll maneuver air-loads
- Debris analysis flow-fields
- 3% Shuttle wind-tunnel test loads prediction

Approach

- Overflow RANS flow solver
  - Central-differencing + scalar dissipation, 2nd order
  - Diagonalized approximate factorization implicit scheme
  - Spalart-Allmaras turbulence model
  - Multi-level parallelism, scalable to hundreds of CPUs
  - Use full-multi-grid sequencing to get started
- Overset (Chimera) gridding approach
  - Developed an automated grid-generation capability
  - Gimble angles for SSME and SRB nozzles
  - Control surface deflections
  - Plume boundary-condition generation for SSMEs and SRBs
- Validation with 3% WT model: Cp, PSP, PIV

CFD Analysis of SSLV Ascent

Results

- Over 400 Overflow solutions run for Return-to-Flight
- New grids generated for each ascent condition
  - 2 hours on 32 Itanium-2 CPUs
  - 30 to 50 million grid points each
- Average of ~1000 Itanium-2 CPU hrs / solution
  - ~20 hours of wallclock time running on 64 Itanium-2 CPUs
  - Never converges to a steady-state: aft end of ET, attachment hardware, plumes, etc
  - Typically run for ~10,000 iterations

Geometry Details







“Columbia”: World Class Supercomputing

- The NAS houses the world’s fastest operational supercomputer providing 61 teraflops of compute capability to the NASA user community
- Columbia is a 20-node supercomputer built on 512-processor nodes
- Columbia is the largest SGI system in the world with over 10,000 Intel Itanium2 processors

IA-700 Wind Tunnel Tests

ARC 9x7 Unitary, AEDC 16T



Wind Tunnel Test Comparisons - Orbiter Wing, Y = -380 inches

CFD - SA conditions: $M_\infty = 1.550$, $\alpha = 0.00°$, $\beta = 0.00°$, Reynolds # = 2.50×10^6/ft, IB elevon = 10.00°, OB elevon = -2.00°

IA700A PSP conditions: $M_\infty = 1.550$, $\alpha = 0.00°$, $\beta = 0.00°$, Reynolds # = 2.50×10^6/ft, IB elevon = 10.00°, OB elevon = -2.00°

IA700B PSP conditions: $M_\infty = 1.550$, $\alpha = 0.00°$, $\beta = 0.00°$, Reynolds # = 2.50×10^6/ft, IB elevon = 10.00°, OB elevon = -2.00°

IA700A conditions: $M_\infty = 1.550$, $\alpha = 0.03°$, $\beta = 0.00°$, Reynolds # = 2.50×10^6/ft, IB elevon = 10.00°, OB elevon = -2.00°, Run = 890, Point = 6, LOX Roll = 15°

IA700B conditions: $M_\infty = 1.550$, $\alpha = -0.33°$, $\beta = -0.27°$, Reynolds # = 2.50×10^6/ft, IB elevon = 10.00°, OB elevon = -2.00°, Run = 212, Point = 4, LOX Roll = 0°



Wind Tunnel Test Comparisons - External Tank - Phi = 203.75°

CFD - SA conditions: $M_\infty = 1.550$, $\alpha = 0.00°$, $\beta = 0.00°$, Reynolds # = 2.50×10^6/ft, IB elevon = 10.00°, OB elevon = -2.00°

IA700A PSP conditions: $M_\infty = 1.550$, $\alpha = 0.00°$, $\beta = 0.00°$, Reynolds # = 2.50×10^6/ft, IB elevon = 10.00°, OB elevon = -2.00°

IA700B PSP conditions: $M_\infty = 1.550$, $\alpha = 0.00°$, $\beta = 0.00°$, Reynolds # = 2.50×10^6/ft, IB elevon = 10.00°, OB elevon = -2.00°

IA700A conditions: $M_\infty = 1.550$, $\alpha = 0.03°$, $\beta = 0.00°$, Reynolds # = 2.50×10^6/ft, IB elevon = 10.00°, OB elevon = -2.00°, Run = 890, Point = 6, LOX Roll = 15°

IA700B conditions: $M_\infty = 1.550$, $\alpha = -0.33°$, $\beta = -0.27°$, Reynolds # = 2.50×10^6/ft, IB elevon = 10.00°, OB elevon = -2.00°, Run = 212, Point = 4, LOX Roll = 0°



STS-50 Orbiter wing running loads

Mach 1.25, Alpha -3.3, Beta 0.0, $\delta_{ei/o}$ = 10.5/6.25, Qbar=640.7 psf







J. Greathouse/JSC

IA-700 Transonic PSP vs. CFD

- Mach = 1.55, α = 0°, β = 0°
  - Lighting & camera angles reduced measurement quality in ET nose and Orbiter lower surface regions





ARC 9 × 7 Mach 2.5 PIV Comparison



OVERFLOW solution – S. Rogers/ARC



Optical distortion from ET bow shock caused PIV inaccuracies

Window glare results in artificial low velocity regions



Cart3D solution – M. Aftosmis/ARC



Post STS-114 Solutions

Addition of Ice/Frost Ramps



Debris Impact Assessment Process



Debris Transport Analysis

Debris Source



Damage Assessment

Debris Transport Process Overview



Debris Transport

- Ballistic debris integration:
  - Steady-state CFD flowfield
  - Integrate motion of point-mass subject to drag force due to relative local wind vector at current location in the flowfield
  - Neglects effect of cross-range dispersions due to lift
- Debris Transport software development:
  - Developed debris-drag models using Cart3D 6-DOF unsteady simulations
  - Significant improvements to debris-trajectory computations
  - Wrote software for debris collision and proximity detection
  - Wrote general purpose sorting and filtering of collision output
- Millions of debris trajectories have been computed and analyzed





Debris Code Analysis Options



Deterministic
Zero Lift Trajectory + Range of Initial Velocities

LH_2 Flange Foam
Mass = 0.023 lb_m
ρ_{foam} = 2.34 lb/ft^3
$V_{pop\text{-}off}$ = 113 ft/sec



Cross range = f(shape, mass, rotation rate/orientation)

Probabilistic
Zero Lift Trajectory + Crossrange Cone

Time History





Debris Aerodynamics Modeling

- Debris Transport currently requires two aerodynamic models for each type of debris to be analyzed:
  - **Drag model :** determines impact velocity
  - **Cross-range model** : determines impact locations
- Impractical to determine model parameters using experimental techniques (too costly, time consuming, restricted to simple shapes).
- Use validated CFD methods (cheap, rapid turnaround, not restricted by geometry shapes).
- Compute hundreds of 6-DOF trajectories using a Monte-Carlo approach (vary shape, orientation, rotation rate) and model the resulting behavior.
- Have developed drag and cross range models for:
  - Tumbling cube
  - Foam divots (based on a conical frustum model)
  - Ablator material
  - Hemisphere, to model ice balls



Cart3D

- Automated mesh generation from CAD
- Partitioned on the fly for any number of CPUs
- Solves Euler equations:
  - Unstructured Cartesian cells
  - Finite-volume formulation
  - Multi-grid acceleration
  - Shared-memory parallelization w/ OpenMP
  - 4.5 million cells, 15 levels of refinement



- Drag modeling uses 6-DOF data
- Kinetic energy (damage potential) used as “fitness function”
- Drag model validated against Ames GDF range data
  - Drag models created Feb. ‘04
  - These models were used in the design of all the validation experiments

Drag



Kinetic Energy



Foam Cross-Range Model

- Debris can generate aerodynamic “lift” in arbitrary direction during trajectory (referred to as crossrange).
- This effect is modeled in a post-processing step.
- Crossrange cone applied to zero-lift debris trajectories from ballistic code to determine possible impact points.



Foam Cross-Range Data

- Data from Monte-Carlo CFD 6-DOF trajectories used to develop crossrange cone.
- Several shapes used to develop crossrange behavior.
- Results can be scaled to arbitrary-sized debris.
- A probability can be assigned to any location within crossrange cone.



Validation With Gun Development Facility (GDF) Data

- There are two aspects to the validation effort:
  - Validate the ability of the Cart3D code to simulate a 6-DOF foam trajectory by direct comparison against range data. (validation of CFD method)
  - Validate the foam drag and cross-range models using the range data. (validation of models)

Ames Gun Development Facility

1.75" Powder Gun and Dump Tank

Side-View Cameras and Controllers



Sabot and Projectile



Test Section - Diaphragm, Lights, Light Screens, and Calibration Grids

Jeff Brown - Eloret/Code ASA
650-604-6192 / jbrown3@mail.arc.nasa.gov

6-DOF Method Validation
Ames GDF ballistic data Distance vs Time

- Mach 2.51, 6000 g's deceleration



6-DOF Method Validation

Ames GDF ballistic data Pitch/Yaw vs Time

Shot 3, Untripped





Shot 5, Tripped



Drag Model Validation

- Low oscillation trajectory - shot 2, Mach = 3.00



Drag Model Validation

- Medium oscillation trajectory - shot 7, Mach = 2.81



Drag Model Validation

- High oscillation trajectory - shot 6, Mach = 2.46



- Cart3D 6-dof predictions bound ballistic data
  - CFD (all) represents several hundred CFD trajectories generated from offset C.G. and asymmetric models
    - CFD data is used in dprox code to determine potential impact cone
- Even mild asymmetry generates strong crossrange





CUBRC Setup





View looking back upstream



Run 9
5.1 inch divot AR 5.4
Mach 3.5 Q 706 psf

What the two pieces looked like several feet down stream





Run12$_{-h1}$

Run 12
7.4 inch divot
AR 7.8
Mach 3.5
Q 729 psf

DFRC F-15B



BX-265
foam sheets



Flight Test Fixture

Results from F-15B Testing

- Conducted 9 flights using BX-265 foam sheets
  - Total of 38 divots liberated
- All 31 of the supersonic divots 'trimmed'
  - Of these, 30 of 31 rotated leading edge away from the sheet trimming with the small diameter facing forward
    - Divot C at Mach 1.6 and 850 psf passed through this first trim point and trimmed with the large diameter forward (only divot to behave in this fashion)
  - 2 of the 5 subsonic divots tumbled after one oscillation
- 36 divots survived the aerodynamic deceleration associated with being ejected into the flow field
  - Two of the three divots generated using the lowest successful ejection pressure rotated back into the sheet
    - As a result of re-contact with the sheet, the divots fractured into several pieces
  - Ejection pressure did not appear to affect divot geometry
    - All divots tended to be slightly smaller than predicted (using 30° angle assumption)

1-dof Comparison to F-15B Data



STS-114 Ice/Frost Ramp Debris Event

Computed and Enhanced Video Trajectories





Mass = 0.03 lbm, 30 ft/sec pop-off velocity

Trajectory, 0.03 lbm

30 ft/sec pop-off velocity





Mass=0.03 lbm Trajectories

0 – 10 ft/sec pop-off velocity



LH2 PAL Ramp Foam Debris

- LH2 PAL ramp release conditions at SRB Sep +5 sec
  - Mach=4.19, Qbar=19.5, α = 1.23 deg, β = -0.87 deg
- Mass estimated ~= 0.98 lbm
- BX-265 Foam density = 2.34 pcf




LH2PALRamp RCC Maximum Kinetic Energy Hits
Nominal Foam-Debris Drag Model, Thickness range = 4.0 - 6.0 in.
Flow Conditions = m4.200a5.319b0.000pl
Qbar adjusted to 20 psf
Kinetic Energy, ft-lb
2000
1800
1600
1400
1200
1000
800
600
400
200
1.200 lbm
1.100 lbm
1.000 lbm
0.900 lbm
0.800 lbm
22 18 14 10 6 2 2 6 10 14 18 22
Port Wing RCC
RCC Panel Number
Starboard Wing RCC

Mass=1.0 lbm Trajectories



Only outer edge of cone intersects wing:
low probability of hitting wing

Concluding Remarks

- CFD simulations of SSLV ascent have become a value data tool for the program
  - Significant computational and experimental validation efforts
- Deterministic debris transport simulation has been used to quantify the debris environment during ascent
  - Being extended to reentry cases
- Probabilistic debris simulation capability under development, significantly aided by CFD simulations